

RIGHT OF WAY STAKING PLAN

INITIAL MONUMENTS SET PRIOR TO CONSTRUCTION.
 FINAL MONUMENTS WILL BE SET AT THE END OF CONSTRUCTION.
 FOR ADDITIONAL INFORMATION SEE RESULTS OF SURVEY
 AS SHOWN ON SHEETS RS-1 TO RS-3

ROS subtitle
TEXT
 LV=225 FT=23
 CO=25 TX=22.5
 LC=0 ACTIVE
 WT=4 TXJ=CT

PLAN SHEET NOTES
 SEED FILE: 2DSeed.dgn
 FILE NAME: --rw--_rs06.dgn
 REFERENCE FILES:
 --rw--_bdr.dgn
 --rw--_pln.dgn
 --rw--_rs02.dgn
 AA=0 AS=5 RV=As needed
 See plotting instructions
 in CADD Standards Manual
 for additional details.

HELPFUL HINTS
 Construction project limits will be shown, for those R/W projects that have multiple segmented or phased smaller construction projects that are contained within the greater R/W plan limits.

REFERENCE FILE
 --rw--_pln.dgn
 Attachment: Coincident
 See Exhibits E1 through E6 for linestyle settings etc. for this reference file.

REFERENCE FILE
 --rw--_rs02.dgn
 Attachment: Coincident
 See Exhibit F3. Also see note below for further instructions.

REFERENCE FILE
 --rw--_pln.dgn
 Attachment: Coincident
 See Exhibits E1 through E6 for linestyle settings etc. for this reference file.

HELPFUL HINTS
 The Right of Way Monumentation Staking Plan is a temporary sheet that will be created as part of the setting of temporary right of way monuments prior to construction. This sheet and an ASCII file that contains the points shown hereon will be forwarded to the contractor so that they are aware of the permanent monuments that need to be set.
 This sheet will be converted into the Right of Way Monumentation Survey plan sheets at the end of construction which will indicate that the permanent monuments set during construction are in the correct position.

HELPFUL HINTS
 Point 2102 is an example of when a new R/W monument will be set on the existing R/W at a highway control point location. Typically, this will be done if no ADOT monument previously existed, or if the existing monument was originally set incorrectly by an unacceptable amount.

Note:
 The original Results of Survey sheet with all levels except 225 being turned off and its reference files will be referenced to the Right of Way Monumentation Staking Plan.
 Several levels will need to be turned on or off on the planlinework file as needed.


HELPFUL HINTS
 Leave the Description field blank until after the final monuments have been set.

HELPFUL HINTS
 Stations and Offsets shown in the monumentation list table should exactly match those shown for the corners on the R/W plans and/or Results of Survey.

PT.	NORTHING	EASTING	DESCRIPTION	STATION	OFFSET
100	796856.32200	475554.09654		6063+90.73	125.00' LT
101	797114.23000	475308.61544		6066+01.76	396.11' LT
102	798385.71000	475534.34434		6078+93.12	373.97' LT
103	801070.78293	475635.51586		6105+50.93	746.90' LT
104	802287.59511	476302.03716		6118+69.13	300.00' LT
105	804924.92796	476770.24564		6145+40.19	300.00' LT
106	807562.79268	477238.54853		6172+26.81	300.00' LT
108	797059.24941	475902.34344		6066+51.47	200.00' RT
109	797726.85426	475999.98851		6073+25.81	200.00' RT
110	799669.26718	476344.85666		6092+95.42	200.00' RT
111	802282.45311	476808.81801		6119+53.48	200.00' RT
112	804919.25945	477276.97313		6146+30.70	200.00' RT
113	807556.97404	477767.89332	See Note 3	6173+13.61	222.00' RT
114	807557.95200	477669.34300		6172+91.46	125.00' RT
115	804919.00711	477299.53217		6146+34.39	222.00' RT
118	797069.44939	474449.84145	See Note 1	6064+07.54	1244.94' LT
119	797149.38194	474453.12589	See Note 1	6064+86.82	1250.17' LT
120	798076.65570	476062.09445	See Note 3	6076+81.08	200.00' RT
121	799107.83824	476245.17705		6087+28.24	200.00' RT
2100	808860.14548	477900.70526	See Note 2	6186+19.96	125.00' RT
2102	808895.13200	477703.79000	See Note 2	6186+19.96	75.00' LT

NOTES
 1/2" rebars with plastic cap PLS*19817 set as temporary monuments for each of the points shown unless otherwise noted.
 The contractor is responsible for maintaining and replacing any temporary monuments that are destroyed during construction.
 1) 1/2" Rebar w/ plastic cap PLS *19817 set for final R/W Monument. Standard ADOT R/W monument NOT to be set at this location.
 2) Set standard ADOT R/W monument for final R/W monument
 3) Unable to set temporary monument.

STANDARD ADOT R/W MONUMENT DETAIL
 Unless otherwise noted, all set monuments are 3" aluminum cap on 3/4" rebar. Typical stamping below.



HELPFUL HINTS
 The standard ADOT R/W monument detail is only added to the sheet when final R/W monuments are also being set on existing R/W corners that are located on the sheet.

RW_V8.cel
 AC=LEGND2
 LV=Varies
 CO=Varies
 LC=Varies
 WT=Varies

REFERENCE FILE
 --rw--_bdr.dgn
 Attachment: Saved View = Border
 SEE EXHIBIT B1 FOR DETAILS

EXHIBIT-F10 ADOT CADD STANDARDS 2006

CHANGE ORDER REVISIONS		DESCRIPTION OF REVISIONS		DRAWING NO. D-7-T-940		ARIZONA DEPARTMENT OF TRANSPORTATION INTERMODAL TRANSPORTATION DIVISION RIGHT OF WAY PLANS SECTION	
C.O. NO.				SURVEY	October 2001	HIGHWAY NAME:	GILA BEND - BUCKEYE
				DRAWN/DATE	J. Crume/Sep 01	FEDERAL AID NO.:	S 085-B-701
				ADOT REVIEW	B. Gurney	PROJECT NO.:	085 MA 138 H5675 02R
				HUBBARD ENGINEERING 480-892-3313 Gilbert, AZ jcrume@heaz.us Job # 20047		PRELIMINARY NOT FOR CONSTRUCTION OR RECORDING --Created-- 9/9/2009 9:29:37 AM	
				ROUTE NO.:	S.R. 85	LOCATION:	Lewis Prison - Gila River

REFER TO THE RESULTS OF SURVEY AND R/W PLANS FOR THE BASIS OF STATIONING.

0 250 500
 Scale

exhibitf10_rs06.dgn